

Product data sheet for household cooker hoods according to regulation (EU) No. 65/2014		
Brand	PYRAMIS	
Model	065028602	
Annual Energy Consumption (AEC_{hood})	kWh/a	94
Energy Efficiency Class		D
Fluid Dynamic Efficiency (FDE_{hood})		6,5
Fluid Dynamic Efficiency Class		F
Lighting Efficiency (LE_{hood})	lux/W	13
Lighting Efficiency Class		D
Grease Filtering Efficiency (GFE)	%	70
Grease Filtering Efficiency Class		D
Air Flow at minumum speed in normal use	m ³ /h	165
Air Flow at maximum speed in normal use	m ³ /h	300
Air Flow in use intensive or boost setting	m ³ /h	-
Acustic Power emission in normal use at minimum speed	dB	57
Acustic Power emission in normal use at maximum speed	dB	65
Acustic Power emission in boost mode	dB	-
Power Consumption in off mode (P_o)	W	0
Power Consumption in standby mode (P_s)	W	-
Integration Directive EU 66/2014		
Time Increase Factor (f)		1,8
Energy Efficiency (EEI_{hood})		98,7
Airflow at best efficiency point (Q_{BEP})	m ³ /h	193
Pressure at best efficiency point (P_{BEP})	Pa	171
Electric power input at the best efficiency point (W_{BEP})	W	140
Electric power input for lighting system (W_L)	W	5
Avarage illuminance on the cooking surface (E_{middle})	lux	65

Product data sheet for household cooker hoods according to regulation (EU) No. 65/2014			
Brand		PYRAMIS	
Model		065028602	
Annual Energy Consumption (AEC_{hood})		kWh/a	94
Energy Efficiency Class			D
Fluid Dynamic Efficiency (FDE_{hood})			6,5
Fluid Dynamic Efficiency Class			F
Lighting Efficiency (LE_{hood})		lux/W	13
Lighting Efficiency Class			D
Grease Filtering Efficiency (GFE)		%	70
Grease Filtering Efficiency Class			D
Air Flow at minumum speed in normal use		m ³ /h	165
Air Flow at maximum speed in normal use		m ³ /h	300
Air Flow in use intensive or boost setting		m ³ /h	-
Acustic Power emission in normal use at minimum speed		dB	57
Acustic Power emission in normal use at maximum speed		dB	65
Acustic Power emission in boost mode		dB	-
Power Consumption in off mode (P_o)		W	0
Power Consumption in standby mode (P_s)		W	-
Integration Directive EU 66/2014			
Time Increase Factor (f)			1,8
Energy Efficiency (EEI_{hood})			98,7
Airflow at best efficiency point (Q_{BEP})		m ³ /h	193
Pressure at best efficiency point (P_{BEP})		Pa	171
Electric power input at the best efficiency point (W_{BEP})		W	140
Electric power input for lighting system (W_l)		W	5
Avarage illuminance on the cooking surface (E_{middle})		lux	65